

Amdt. dated August 11, 2003

Reply to Office Action of February 13, 2003

**Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

**Listing of Claims:**

Sub  
D1

1. (Currently Amended) An apparatus for interfacing video information, comprising:  
a main body, which outputs a video signal and corresponding display type information, the display type information including a recognition code that does not correspond to a memory address for designating a kind of the corresponding display type information, and data corresponding to the recognition code; and

a monitor, which detects a display type of the corresponding video signal in accordance with the display type information, and displays the video signal outputted from the main body in accordance with the detected display type.

C1

2. (Currently Amended) A video interface, comprising:  
a main body, which outputs a video signal through a video signal line, and outputs information relating to the video signal display type, the information relating to the video signal display type including a display code that designates the video signal display type, wherein the display code comprises a recognition code that does not correspond to a memory address for designating a kind of the corresponding video signal display type information, and the information corresponding to the recognition code; and

Amdt. dated August 11, 2003

Reply to Office Action of February 13, 2003

a monitor, which detects the display type of the corresponding video signal in accordance with the display information, and displays the video signal outputted from the main body in accordance with the detected display type.

3. Cancelled

4. (Previously Presented) An apparatus for interfacing video information in a computer system, comprising:

a main body, which outputs a video signal, a horizontal sync signal, a vertical sync signal, and video signal display type information identifying a video type of the video signal, the video signal display type information including a display code that designates the video signal display type, wherein the video signal display type information is divided to comprise divided display type information having at least two parts, and wherein the divided display type information is embedded into the horizontal sync signal and at least one of R, G, and B video signals forming the video signal, respectively; and

a monitor, which detects the type of display for the corresponding video signal in accordance with the display type information, and displays the outputted video signal in accordance with the detected display type.

Amdt. dated August 11, 2003

Reply to Office Action of February 13, 2003

5. (Previously Presented) A video interface, comprising:

a main body, which provides information relative to a display type of a video signal, the information being divided to comprise divided display type information having at least two parts, wherein a first part of the divided display type information is embedded into one of a horizontal sync signal and a vertical sync signal, and wherein a second part of the divided display type information is embedded into at least one of R, G, and B video signals comprising the video signal, respectively, and outputs the video signal, the horizontal sync signal, and the vertical sync signal; and

C\ a monitor which detects the display type of the corresponding video signal in accordance with the display type information outputted from the main body, and displays the video signal in accordance with the detected display type, wherein the information relative to the display type comprises a display code that designates the video signal display type.

6. Cancelled

7. Cancelled

8. (Previously Presented) A method of interfacing video information, comprising:

transmitting video signal display type information, horizontal and vertical sync signals, and a video signal from a main body to a monitor, the video signal display type

Amdt. dated August 11, 2003

Reply to Office Action of February 13, 2003

information being divided to comprise divided display type information having at least two parts, and wherein a first part of the divided display type information is embedded into one of the horizontal sync signal and the vertical sync signal, and wherein a second part of the divided display type information is embedded into at least one of R, G, and B video signals comprising the video signal, respectively, the video information display type information including a display code that designates a video display type; and

detecting a display type of the video signal transmitted from the main body using the video signal display type information, and displaying the video signal to match the display type.

C1 9. (Previously Presented) The method as claimed in claim 8, wherein the display type information comprises a recognition code for designating a kind of the corresponding display type information, and data corresponding to the recognition code.

10. (Original) The method as claimed in claim 9, wherein the recognition code is composed of two bits.

11. (Original) The method as claimed in claim 9, wherein the data includes a number of dots in a horizontal period, a number of backporches in the horizontal period, a number of

Amdt. dated August 11, 2003

Reply to Office Action of February 13, 2003

horizontal lines in a vertical period, and a number of horizontal lines of a backporch in the vertical period.

12. (Currently Amended) A method of interfacing video information, comprising:  
transmitting display type information of a video signal in communication data, along with horizontal and vertical sync signals from a main body to a monitor, the display type information comprising a display code that designates a video signal display type, wherein the display code comprises a recognition code that does not correspond to a memory address for designating a kind of the corresponding display type information, and data corresponding to the recognition code; and

C detecting a display type of the transmitted video signal using the display type information, and displaying the video signal to match the display type.

13. (Original) The method as claimed in claim 12, wherein the display type information is synchronized with the vertical sync signal.

14. (Previously Presented) A method of interfacing video information, comprising:  
dividing display type information of a video signal into at least two parts;

Amdt. dated August 11, 2003

Reply to Office Action of February 13, 2003

transmitting divided display type information of the video signal in each of a horizontal sync signal and the video signal, respectively, from a main body, the display type information including a display code that designates the video signal display type; and

detecting a display type of the transmitted video signal using the display type information.

15. (Original) The method as claimed in claim 14, wherein the main body synchronizes the display type information with the vertical sync signal.

C1 16. (Previously Presented) The method as claimed in claim 14, further comprising transmitting a vertical sync signal from the main body to the monitor, wherein the vertical sync signal comprises a clock pulse for recognizing the display type information.

17. (Previously Presented) A method of interfacing video information, comprising:  
dividing display type information of R, G, B video signals, the display type information including a recognition code that designates the video signal display type and data corresponding to the recognition code;

embedding the divided display type information into a horizontal sync signal and at least one of the R, G, and B video signals, respectively;

Amdt. dated August 11, 2003

Reply to Office Action of February 13, 2003

transmitting to a monitor the horizontal sync signal, a vertical sync signal, and the video signals;

decoding and reassembling the display type information; and

detecting a display type of the transmitted video signal using the reassembled display type information.

18. (Original) The method as claimed in claim 17, wherein the main body synchronizes the display type information with the vertical sync signal.

19. (Original) The method as claimed in claim 17, wherein a clock pulse for recognizing the display type information is included in the vertical sync signal.

20. Cancelled

21. Cancelled

22. (Original) The device of claim 1, wherein the display information comprises a number of dots for a horizontal period, a number of backporches for the horizontal period, a number of horizontal lines for a vertical period, and a number of horizontal lines of a backporch for the vertical period.

Amdt. dated August 11, 2003

Reply to Office Action of February 13, 2003

23. (Original) The device of claim 1, wherein the video signal comprises a RGB signal, a horizontal sync signal, and a vertical sync signal.

24. (Previously Presented) The device of claim 1, wherein the display information is further transmitted in serial data.

25. Cancelled

C1  
26. (Currently Amended) An apparatus for interfacing video information, comprising:  
a computer transmitting horizontal and vertical sync signals, serial data signal and serial clock signals through a display data channel, and a video signal; and  
a monitor receiving the horizontal and vertical sync signals, serial data signal and a serial clock signal through the display data channel, and the video signal, wherein a display type information of the video signal, including a display code that designates the video signal display type, is included in one of the serial data signal of the display data channel and the horizontal sync signal, wherein the display code comprises a recognition code that does not correspond to a memory address for designating a kind of the corresponding video signal display type data, and data corresponding to the recognition code.



Amdt. dated August 11, 2003

Reply to Office Action of February 13, 2003

27. (Previously Presented) A method of interfacing video information, comprising:  
dividing display type information of a video signal, the display type information including a display code that designates a video signal display type;  
embedding the divided display type information into at least one of a horizontal sync signal, an R video signal, a G video signal, and a B video signal;  
embedding a clock pulse for recognizing the display type information in a vertical sync signal;  
transmitting the horizontal sync signal, the R video signal, the G video signal, the B video signal, and the vertical sync signal from a main body to a monitor; and  
detecting the video signal display type using the display type information.

28. (Previously Presented) The method of claim 27, wherein the display code comprises a recognition code that designates the video display type and data corresponding to the recognition code.

29. (Previously Presented) The apparatus of claim 1, wherein the main body outputs a vertical sync signal including a clock pulse for recognizing the display type information.

30. Cancelled

Amdt. dated August 11, 2003

Reply to Office Action of February 13, 2003

31. Cancelled

32. (Previously Presented) The apparatus of claim 2, wherein the main body outputs a vertical sync signal including a clock pulse for recognizing the display type information.

33. (Previously Presented) The apparatus of claim 4, wherein the display code comprises a recognition code that designates the video display type and data corresponding to the recognition code.

C1 34. (Previously Presented) The apparatus of claim 4, wherein the vertical sync signal comprises a clock pulse for recognizing the display type information.

35. (Previously Presented) The apparatus of claim 5, wherein the display code comprises a recognition code that designates the signal display type and data corresponding to the recognition code.

36. (Previously Presented) The apparatus of claim 5, wherein the vertical sync signal comprises a clock pulse for recognizing the display type information.

Amdt. dated August 11, 2003

Reply to Office Action of February 13, 2003

37. (Previously Presented) The method of claim 8, wherein the display code comprises a recognition code that designates the video display type and data corresponding to the recognition code.

38. (Previously Presented) The method of claim 8, wherein the vertical sync signal comprises a clock pulse for recognizing the display type information.

39. Cancelled

40. (Previously Presented) The method of claim 12, wherein the vertical sync signal comprises a clock pulse for recognizing the display type information.

41. (Previously Presented) The method of claim 14, wherein the display code comprises a recognition code that designates the video signal display type and data corresponding to the recognition code.

42. Cancelled

43. (Previously Presented) The apparatus of claim 26, wherein the vertical sync signal comprises a clock pulse for recognizing the display type information.

Amdt. dated August 11, 2003

Reply to Office Action of February 13, 2003

44. (Previously Presented) The apparatus as claimed in claim 1, wherein the display type information is divided to comprise at least two parts, and wherein the divided display type information is embedded into a horizontal sync signal and at least one of the R, G, and B video signals, respectively.

45. (Previously Presented) The interface as claimed in claim 2, wherein the information relating to the video signal display type is divided to comprise divided display type information having at least two parts, and wherein the divided display type information is embedded into a horizontal sync signal and at least one of the R, G, and B video signals, respectively.

46. (Previously Presented) The method as claimed in claim 12, wherein the display type information is divided to comprise divided display type information having at least two parts, and wherein at least one part of the divided display type information is embedded into one of a horizontal sync signal and at least one of the R, G, and B video signals, respectively.

47. (Previously Presented) The method of claim 14, wherein the display type information comprises a recognition code for designating a kind of the corresponding display type information, and data corresponding to the recognition code.

Amdt. dated August 11, 2003

Reply to Office Action of February 13, 2003

48. (Previously Presented) The apparatus as claimed in claim 26, wherein the display type information is divided to comprise divided display type information having at least two parts, and wherein the divided display type information is embedded into a horizontal sync signal and at least one of the R, G, and B video signals, respectively.

CA 49. (New) The apparatus of claim 1, wherein the plurality of data types comprises at least one of a number of dots for a horizontal period, a number of backporches for the horizontal period, a number of horizontal lines for a vertical period, and a number of horizontal lines of a backporch for the vertical period, and wherein each of the plurality of data types has a unique recognition code associated therewith.

50. (New) The interface of claim 2, wherein the plurality of data types comprises at least one of a number of dots for a horizontal period, a number of backporches for the horizontal period, a number of horizontal lines for a vertical period, and a number of horizontal lines of a backporch for the vertical period, and wherein each of the plurality of data types has a unique recognition code associated therewith.

51. (New) The method of claim 12, wherein the plurality of data types comprises at least one of a number of dots for a horizontal period, a number of backporches for the horizontal period, a number of horizontal lines for a vertical period, and a number of horizontal

Serial No. 09/628,503

Docket No. K-0191

Amdt. dated August 11, 2003

Reply to Office Action of February 13, 2003

lines of a backporch for the vertical period, and wherein each of the plurality of data types has a unique recognition code associated therewith.

52. (New) The apparatus of claim 26, wherein the plurality of data types comprises at least one of a number of dots for a horizontal period, a number of backporches for the horizontal period, a number of horizontal lines for a vertical period, and a number of horizontal lines of a backporch for the vertical period, and wherein each of the plurality of data types has a unique recognition code associated therewith.

---